



IM-o46o-22 Ice Cube Machine

Models

☐ IM-o46o-AC-22 ☐ IM-o46o-AH-22



ICETRO IM-o46o-22 ice machine on a IB-o26-22 bin

*Ice Machine and Bin sold separately

- Up to 443 lbs production capacity (70F/50F, 24 Hours)
- 304 stainless-steel exterior (durable & rust-resistant)
- Simple diagnostic panel to assist service & maintenance
- Cleaning switch for auto cleaning cycle
- Magnetic frame cleanable condenser air filters
- Adjustable flush time to reduce scale & cleaning cost
- ABS antimicrobial interior to reduce slime & cleaning cost
- Water distributor tube & water sump removed w/o tools
- Heavy duty water curtain, pins & hangers for easy removal
- Hinged front doors for easy access
- No screws on side or back panels for easy access
- Sides & top vents for optimal ventilation
- Improved evaporator section to reduce airborne bacteria
- Power cord with NEMA 5-15 plug
- R-404A refrigerant

Ice Shape



Half Cube
 $\frac{3}{8}" \times 1\frac{1}{8}" \times \frac{7}{8}"$
 (.95" x 2.86" x 2.22 cm)



Cube
 $\frac{7}{8}" \times \frac{7}{8}" \times \frac{7}{8}"$
 (2.22" x 2.22" x 2.22 cm)

Factory Warranty

Parts & Labor **Parts**
3 YR **5 YR** **5 YR**
 Ice Maker Evaporator Compressor



Extend parts & labor warranty 1 year by installing an IcePro filter/cartridge and by registering it at: icetrowaterproducts.com/registration/

* Applies only to new ice machines, at the time of original installation & start-up.

** Requires replacement of the filter cartridge every 6 months or earlier

Specifications

BTU Per Hour:

5,405

Refrigerant:

R404A

- Ambient Temperature Range: 50 to 100 F (10 to 37 C)
- Water Temperature Range: 50 to 90 F (10 to 32 C)
- Potable Water Pressure: Min. 20 psi (137.9 kPa) Max. 80 psi (551.1 kPa)
- Condenser Water Pressure: Min. 20 psi (1.38 bar) Max. 150 psi (10.34 bar)

Ice Machine Electric

115/60/1

Minimum circuit ampacity:

Air-cooled: 15 *1ph*

Maximum fuse size:

Air-cooled: 20 *1ph*

Accessories

Bin Adapter

IBT-223oB Center Mount 30" Bin*
 IBT-223oBV Center Mount 30" Bin

* Bins with S/N prior to VA/JJ

Bin-Stat Kit

IBO-15oKIT

Recommended when ice machine is installed on soda dispenser.



Water Filtration

IcePro 500 (replaces IcePro 400)


Reduces sediment and chlorine contaminants with the use of Citrine.





IM-o46o-22 Ice Cube Machine

IM-0460-22 Air Cooled



Specifications

Dimensions		Width	Depth	Height	Weight	
IM-0460-22 Machine		22"	24.8"	22.6"	143.3 lbs (Net)	168 lbs (Shipping)

AIR COOLED	Model	Ice Shape	Ice Production 24 Hours		Power Usage kWh/100 lbs. @90° Air/70°F	Potable Water Usage/100 lbs. 45.4 kgs. of Ice
			70° Air/ 50°F Water	90° Air/ 70°F Water		
			1 ph	1 ph	1 Ph	
	IM-0460-AC-22	cube	443 lbs	367 lbs	6.21	18 Gal.
			201 kgs	167 kgs		18 Gal.
	IM-0460-AH-22	half-cube	443 lbs	367 lbs	6.21	18 Gal.
			201 kgs	167 kgs		18 Gal.

